

ER12H-2000

ER12H-2000,
Maxium payload 12kg with maxium reach 2025 mm.

- Highlights
- Thanks to the large and hollow design, the cable can be routed in a hollow way, effectively improving the service life of the cable, and the posture change in a narrow space is more flexible;
High-rigid gearbox with strong impact resistance helps customers challenge various application scenarios;
Thanks to the high stiffness transmission design and advanced trajectory algorithm, the improved robot accuracy performance helps customers to face variety of application scenarios.

- Applications
- It can be used in handling operations, sorting, grinding, polishing, painting, etc.

- Industries
- Suitable for ceramics, plastic, metal parts and other industries.



EFORT Intelligent Robot Co., Ltd.
PHONE: (00 86) 400-052-8877
ADDRESS: No. 96, Wanchun East Road, Wuhu, China
(Anhui) Pilot Free Trade Zone
WWW.EFORT.COM.CN


EFORT

SPECIFICATIONS


Model		ER12H-2000
Type		Articulated
Controlled axes		6 Axes
Max. payload on wrist		12 kg
Repeatability		±0.03 mm
Robot weight		190 kg
Reach		2025 mm
Robot IP grade		IP54 / IP67 (Wrist)
Cabinet IP grade		IP20/ IP54 (Optional)
Drive mode		AC servo drive
Installation		Floor, Upside-down
Installation enviroment	Ambient temperature	0~45 °C
	Ambient humidity	RH≤80% (No dew nor frost allowed)
	Vibration acceleration	4.9 m/s ² (<0.5 G)

Allowable load moment at wrist	J4	22 N·m
	J5	22 N·m
	J6	9.8 N·m
Allowable load inertia at wrist	J4	0.65 kg·m ²
	J5	0.65 kg·m ²
	J6	0.17 kg·m ²
Maximum speed	J1	220°/sec
	J2	180°/sec
	J3	210°/sec
	J4	420°/sec
	J5	420°/sec
	J6	700°/sec
Motion range	J1	±170°
	J2	+77°/-160°
	J3	+175°/-85°
	J4	±190°
	J5	±190°(The connect outside robot body.) ±140°(The connect inside robot body.)
	J6	±450°(The connect outside robot body.) ±220°(The connect inside robot body.)


OPERATING SPACE



BASE MOUNTING SIZE



END FLANGE MOUNTING SIZE



*The final interpretation right belongs to EFORT Intelligent Robot Co., Ltd. Any updates will be made without prior notice.